

What is claimed is:

50B1

- 1. A piezoelectric adtuator comprising piezoelectric elements having different thicknesses stacked on one another.
- 2. A piezoelectric actuator according to Claim 1 which is distorted when a driving signal is input to generate a driving force and in which a piezoelectric element located at a side of the piezoelectric actuator with greater distortion has a thickness smaller than that of a piezoelectric element located at a side of the piezoelectric actuator with smaller distortion.
- 3. A piezoelectric actuator according to Claim 1, wherein at least two of the piezoelectric elements generate vibrations in the same direction.
- 4. A piezoelectric actuator according to Claim 1, wherein the piezoelectric elements are stacked in a direction in parallel with an output portion of the piezoelectric actuator.
- 5. A piezoelectric actuator according to Claim 1, wherein the piezoelectric elements are stacked in a direction perpendicular to the output portion of the piezoelectric actuator.
- 6. A piezoelectric actuator according to Claim 1, wherein the piezoelectric elements are piezoelectric elements for generating a plurality of different vibrations which are synthesized to be used as a driving force.
- 7. A piezoelectric actuator according to Claim 6, wherein the plurality of different vibrations of the piezoelectric

Och J.

elements are generated by respective separate piezoelectric elements.

- 8. A piezoelectric actuator according to Claim 1, wherein the piezoelectric elements include a piezoelectric element for detecting a vibration and wherein the piezoelectric element for detecting a vibration has a thickness different from those of the other piezoelectric elements.
 - 9. An ultrasonic motor comprising:

a piezoelectric actuator formed by stacking piezoelectric elements having different thicknesses; and

- a vibrator having the same thickness as that of the piezoelectric actuator vibrated by a vibration of the piezoelectric actuator.
- 10. A piezoelectric sensor comprising a piezoelectric actuator formed by stacking piezoelectric elements having different thicknesses.
- 11. A piezoelectric sensor according to Claim 10 wherein the piezoelectric actuator is distorted when a driving signal is input to generate a driving force and wherein a piezoelectric element located at a side of the piezoelectric actuator with greater distortion has a thickness smaller than that of a piezoelectric element located at a side of the piezoelectric actuator with smaller distortion.
- 12. An electronic apparatus with a piezoelectric actuator, comprising a piezoelectric actuator according to Claim 1.





Cont.

13. An electronic apparatus with a piezoelectric sensor, comprising a piezoelectric sensor according to Claim 10.

and The Add The